


NEEDLE VALVE (NV)



Double Bonnet Single Bonnet

- End Connection : FPT x FPT
- Female Pipe Thread Size (FPT/MPT) : 1/8" to 2" NPT Female (Taper) Threads
(BSPP / BSPT / ISO / Metric or Any Other Threads on Request)
- Needle Valve With Panel Mounting Arrangement on Request**
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : NV - FPT - FPT - MOC

NEEDLE VALVE TUBE X TUBE (NV)



- End Connection : TOD x TOD
- Tube OD Size (TOD) : From 1/8" OD to 2" OD (Fractional)
From 3mm OD to 38mm OD (Metric)
- Needle Valve With Panel Mounting Arrangement on Request**
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : NV - TOD - TOD - MOC

NEEDLE VALVE ANGLE (NVA)



Threaded Threaded x Tube End

- End Connection : FPT x FPT / TOD X FPT or MPT
- Tube OD Size (TOD) : From 1/8" OD to 2" OD (Fractional)
From 3mm OD to 38mm OD (Metric)
- Female Pipe Thread Size (FPT/MPT) : 1/8" to 2" NPT (Taper) Threads
(BSPP / BSPT / ISO / Metric or Any Other Threads on Request)
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : NVA - FNT - TOD - MOC or NVA - TOD - TOD - MOC

NEEDLE VALVE WITH DRAIN (NVD)




- End Connection : FPT x FPT
- Female Pipe Thread Size (FPT) : 1/8" to 2" NPT Female (Taper) Threads
(BSPP / BSPT / ISO / Metric or Any Other Threads on Request)
- Drain Plug Size : 1/8" to 1/2" NPT Male Plug
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : NVD - FPT - FTP - MOC

MULTI PART NEEDLE VALVE (MPV)



- End Connection : FPT x FPT
- Female Pipe Thread Size (FPT) : 1/8" to 2" NPT Female (Taper) Threads
(BSPP / BSPT / ISO / Metric or Any Other Threads on Request)
- Port Size : 1/2" NPT Female With Male Plug
Number of Port
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : MPV - FPT - FPT - MOC - NO OF PORT

BLOCK AND BLEED VALVE (BBV)



- End Connection : FPT x MPT
- Female Pipe Thread Size (FPT/MPT) : 1/8" to 2" NPT Female (Taper) Threads
(BSPP / BSPT / ISO / Metric or Any Other Threads on Request)
- Drain Port Size : 1/4" NPT Female With Male Plug
- Test Pressure : Upto 6000 PSI / 10000 PSI
- Gland Packing : Standard PTFE (Grafoil for high temperature)
- MOC : SS316, 304 / Alloy 400, 600, C276 etc..
- Model Code (*) : BBV - FPT - MPT - MOC

BALL VALVE (BV)



| | |
|--|--|
| End Connection | : FPT x FPT |
| Female Pipe Thread Size (FPT/MPT) | : 1/4" to 2" NPT Female (Taper) Threads (BSPP / BSPT / ISO / Metric or Any Other Threads on Request) |
| Test Pressure | : Upto 2000 PSI |
| Seat Packing | : PTFE |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : BV - FPT - FPT - MOC |

BALL VALVEHIGH PRESSURE (BVHP)



| | |
|--|--|
| End Connection | : FPT x FPT |
| Female Pipe Thread Size (FPT/MPT) | : 1/4" to 2" NPT Female (Taper) Threads (BSPP / BSPT / ISO / Metric or Any Other Threads on Request) |
| Test Pressure | : Upto 6000 PSI & upto 10000 PSI |
| Seat Packing | : PTFE (Peek Optional) |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : BVHP - FPT - FPT - MOC |

BALL VALVE PANEL MOUNTING (BVPM)



| | |
|-----------------------------|---|
| End Connection | : TOD x TOD |
| Tube OD size (TOD) | : From 1/8" OD to 1" OD (Fractional) From 3mm OD to 25mm OD (Metric) |
| Test Pressure | : Upto 6000 PSI & upto 10000 PSI |
| Seat Packing | : PTFE (Peek Optional) |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : BVPM - FPT - FPT - MOC |

THREE WAY BALLVALVE (3BVPM)



| | |
|-----------------------------|---|
| End Connection | : TOD x TOD x TOD |
| Tube OD size (TOD) | : From 1/8" OD to 1" OD (Fractional) From 3mm OD to 25mm OD (Metric) |
| Test Pressure | : Upto 6000 PSI & upto 10000 PSI |
| Seat Packing | : PTFE (Peek Optional) |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : 3BVPM - FPT - FPT - MOC |

GAUGE COCK 2 Way (GC2)



| | |
|--|--|
| End Connection | : FPT x FPT or MTP x FTP |
| Female Pipe Thread Size (FPT/MPT) | : 1/4" to 1/2" NPT Female (Taper) Threads (BSPP / BSPT / ISO / Metric or Any Other Threads on Request) |
| Test Pressure | : Upto 500 PSI |
| Seat Packing | : PTFE |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : GC2 - FPT - FPT - MOC |

GAUGE COCK 3 Way (GC3)



| | |
|--|--|
| End Connection | : FPT x FPT x FPT or MTP x FTP x FPT |
| Female Pipe Thread Size (FPT/MPT) | : 1/4" to 1/2" NPT Female (Taper) Threads (BSPP / BSPT / ISO / Metric or Any Other Threads on Request) |
| Test Pressure | : Upto 500 PSI |
| Seat Packing | : PTFE |
| MOC | : SS316, 304 / Alloy 400, 600, C276 etc.. |
| Model Code (*) | : GC3 - FPT - FPT - MOC |