

**GAUGE SAVER (GS)**



**Type** : Piston Type / Diaphragm Type  
**End Connection** : FPT x MPT  
**Female Pipe Thread Size (FPT/MPT)** : 1/4" to 1/2" NPT Female ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Pressure Range** : 0.6 bar upto 400 bar  
**Packing Seals** : **Viton 'O' Ring**  
**MOC** : SS316, 304 / Alloy 400, 600, C276 etc..  
**Model Code (\*)** : **GS- FPT - MPT - MOC**

**SNUBBER (SN)**



**End Connection** : FPT x MPT  
**Female Pipe Thread Size (FPT/MPT)** : 1/4" to 1/2" NPT Female ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Pressure Rating** : upto 6000 PSI  
**Packing Seals** : Viton 'O' Ring  
**MOC** : SS316, 304 / Alloy 400, 600, C276 etc..  
**Model Code (\*)** : **SN - FPT - MPT - MOC**

**SYPHON 'Q' TYPE (SP-QT)**



**Type** : Coil Type ( Q Type )  
**Female Pipe Thread Size (FPT/MPT)** : 1/4" to 1/2" NPT Male / Female ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Pipe Size** : 1/4" up to 1/2" Sch. 40 / Sch. 80  
**Socket Weld End Connection (SW)** : 1/4" to 1/2" NB  
**MOC** : SS316, SS 304 & Carbon Steel (CS)  
**Special Certification** : IBR Certification on Request  
**Model Code (\*)** : **SP-QT - FPT - MPT - MOC**

**SYPHON PIG TAIL (SP-PT)**



**Type** : Pig Tail Type  
**Female Pipe Thread Size (FPT/MPT)** : 1/4" to 1/2" NPT Male / Female ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Pipe Size** : 1/4" up to 1/2" Sch. 40 / Sch. 80  
**Socket Weld End Connection (SW)** : 1/4" to 1/2" NB  
**MOC** : SS316, SS 304 & Carbon Steel (CS)  
**Special Certification** : IBR Certification on Request  
**Model Code (\*)** : **SP-PT - FPT - MPT - MOC**

**SYPHON 'U' TYPE (SP-UT)**



**Type** : U Type  
**Female Pipe Thread Size (FPT/MPT)** : 1/4" to 1/2" NPT Male / Female ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Pipe Size** : 1/4" up to 1/2" Sch. 40 / Sch. 80  
**Socket Weld End Connection (SW)** : 1/4" to 1/2" NB  
**MOC** : SS316, SS 304 & Carbon Steel (CS)  
**Special Certification** : IBR Certification on Request  
**Model Code (\*)** : **SP-UT - FPT - MPT - MOC**

**NON RETURN VALVE (NRV)**



**End Connection** : FPT x FPT / TOD X TOD  
**Tube OD Size (TOD)** : From 1/8" OD to 2" OD ( Fractional)  
 From 3mm OD to 38mm OD ( Metric)  
**Female Pipe Thread Size (FPT)** : 1/8" to 2" NPT ( Taper) Threads  
 (BSPP / BSPT / ISO / Metric or Any Other Threads on Request)  
**Test Pressure** : Upto 10000 PSI  
**Seal Ring** : Viton / Neoprene / Silicon  
**MOC** : SS316, SS304, Alloy 400, 600, C276 etc..  
**Model Code (\*)** : **NRV - FPT - FPT - MOC or NVA - TOD - TOD - MOC**